

CDI C Manual

Climate Data Interface
Version 2.3.0
October 2023

Uwe Schulzweida
Max-Planck-Institute for Meteorology

Contents

1. Introduction	5
1.1. Building from sources	5
1.1.1. Compilation	5
1.1.2. Installation	6
2. File Formats	7
2.1. GRIB	7
2.1.1. GRIB edition 1	8
2.1.2. GRIB edition 2	8
2.2. NetCDF	8
2.3. SERVICE	9
2.4. EXTRA	9
2.5. IEG	10
3. Use of the CDI Library	11
3.1. Creating a dataset	11
3.2. Reading a dataset	11
3.3. Compiling and Linking with the CDI library	12
4. CDI modules	13
4.1. Dataset functions	13
4.1.1. Create a new dataset: <code>streamOpenWrite</code>	13
4.1.2. Open a dataset for reading: <code>streamOpenRead</code>	14
4.1.3. Close an open dataset: <code>streamClose</code>	15
4.1.4. Get the filetype: <code>streamInqFiletype</code>	15
4.1.5. Define the byte order: <code>streamDefByteorder</code>	15
4.1.6. Get the byte order: <code>streamInqByteorder</code>	15
4.1.7. Define the variable list: <code>streamDefVlist</code>	16
4.1.8. Get the variable list: <code>streamInqVlist</code>	16
4.1.9. Define a timestep: <code>streamDefTimestep</code>	16
4.1.10. Get timestep information: <code>streamInqTimestep</code>	16
4.1.11. Write a variable: <code>streamWriteVar</code>	17
4.1.12. Write a variable: <code>streamWriteVarF</code>	17
4.1.13. Write a horizontal slice of a variable: <code>streamWriteVarSlice</code>	17
4.1.14. Write a horizontal slice of a variable: <code>streamWriteVarSliceF</code>	18
4.1.15. Read a variable: <code>streamReadVar</code>	18
4.1.16. Read a variable: <code>streamReadVarF</code>	18
4.1.17. Read a horizontal slice of a variable: <code>streamReadVarSlice</code>	18
4.1.18. Read a horizontal slice of a variable: <code>streamReadVarSliceF</code>	19
4.2. Variable list functions	20
4.2.1. Create a variable list: <code>vlistCreate</code>	20
4.2.2. Destroy a variable list: <code>vlistDestroy</code>	20
4.2.3. Copy a variable list: <code>vlistCopy</code>	20
4.2.4. Duplicate a variable list: <code>vlistDuplicate</code>	20

4.2.5.	Concatenate two variable lists: <code>vlistCat</code>	21
4.2.6.	Copy some entries of a variable list: <code>vlistCopyFlag</code>	21
4.2.7.	Number of variables in a variable list: <code>vlistNvars</code>	21
4.2.8.	Number of grids in a variable list: <code>vlistNgrids</code>	21
4.2.9.	Number of zaxis in a variable list: <code>vlistNzaxis</code>	21
4.2.10.	Define the time axis: <code>vlistDefTaxis</code>	22
4.2.11.	Get the time axis: <code>vlistInqTaxis</code>	22
4.3.	Variable functions	23
4.3.1.	Define a Variable: <code>vlistDefVar</code>	23
4.3.2.	Get the Grid ID of a Variable: <code>vlistInqVarGrid</code>	24
4.3.3.	Get the Zaxis ID of a Variable: <code>vlistInqVarZaxis</code>	24
4.3.4.	Get the timestep type of a Variable: <code>vlistInqVarTsteptype</code>	24
4.3.5.	Define the code number of a Variable: <code>vlistDefVarCode</code>	25
4.3.6.	Get the Code number of a Variable: <code>vlistInqVarCode</code>	25
4.3.7.	Define the data type of a Variable: <code>vlistDefVarDatatype</code>	25
4.3.8.	Get the data type of a Variable: <code>vlistInqVarDatatype</code>	25
4.3.9.	Define the missing value of a Variable: <code>vlistDefVarMissval</code>	26
4.3.10.	Get the missing value of a Variable: <code>vlistInqVarMissval</code>	26
4.4.	Key attributes	27
4.4.1.	Define a string from a key: <code>cdiDefKeyString</code>	27
4.4.2.	Get a string from a key: <code>cdiInqKeyString</code>	28
4.4.3.	Define an integer value from a key: <code>cdiDefKeyInt</code>	29
4.4.4.	Get an integer value from a key: <code>cdiInqKeyInt</code>	29
4.4.5.	Define a floating point value from a key: <code>cdiDefKeyFloat</code>	29
4.4.6.	Get a floating point value from a key: <code>cdiInqKeyFloat</code>	30
4.4.7.	Define a byte array from a key: <code>cdiDefKeyBytes</code>	30
4.4.8.	Get a byte array from a key: <code>cdiInqKeyBytes</code>	30
4.5.	User attributes	32
4.5.1.	Get number of attributes: <code>cdiInqNatts</code>	32
4.5.2.	Get information about an attribute: <code>cdiInqAtt</code>	32
4.5.3.	Define a text attribute: <code>cdiDefAttTxt</code>	33
4.5.4.	Get the value(s) of a text attribute: <code>cdiInqAttTxt</code>	33
4.5.5.	Define an integer attribute: <code>cdiDefAttInt</code>	33
4.5.6.	Get the value(s) of an integer attribute: <code>cdiInqAttInt</code>	34
4.5.7.	Define a floating point attribute: <code>cdiDefAttFlt</code>	34
4.5.8.	Get the value(s) of a floating point attribute: <code>cdiInqAttFlt</code>	34
4.6.	Grid functions	35
4.6.1.	Create a horizontal Grid: <code>gridCreate</code>	35
4.6.2.	Destroy a horizontal Grid: <code>gridDestroy</code>	36
4.6.3.	Duplicate a horizontal Grid: <code>gridDuplicate</code>	36
4.6.4.	Get the type of a Grid: <code>gridInqType</code>	36
4.6.5.	Get the size of a Grid: <code>gridInqSize</code>	36
4.6.6.	Define the number of values of a X-axis: <code>gridDefXsize</code>	36
4.6.7.	Get the number of values of a X-axis: <code>gridInqXsize</code>	37
4.6.8.	Define the number of values of a Y-axis: <code>gridDefYsize</code>	37
4.6.9.	Get the number of values of a Y-axis: <code>gridInqYsize</code>	37
4.6.10.	Define the number of parallels between a pole and the equator: <code>gridDefNP</code>	37
4.6.11.	Get the number of parallels between a pole and the equator: <code>gridInqNP</code>	38
4.6.12.	Define the values of a X-axis: <code>gridDefXvals</code>	38
4.6.13.	Get all values of a X-axis: <code>gridInqXvals</code>	38
4.6.14.	Define the values of a Y-axis: <code>gridDefYvals</code>	38

4.6.15. Get all values of a Y-axis: <code>gridInqYvals</code>	39
4.6.16. Define the bounds of a X-axis: <code>gridDefXbounds</code>	39
4.6.17. Get the bounds of a X-axis: <code>gridInqXbounds</code>	39
4.6.18. Define the bounds of a Y-axis: <code>gridDefYbounds</code>	39
4.6.19. Get the bounds of a Y-axis: <code>gridInqYbounds</code>	40
4.7. Z-axis functions	41
4.7.1. Create a vertical Z-axis: <code>zaxisCreate</code>	41
4.7.2. Destroy a vertical Z-axis: <code>zaxisDestroy</code>	42
4.7.3. Get the type of a Z-axis: <code>zaxisInqType</code>	42
4.7.4. Get the size of a Z-axis: <code>zaxisInqSize</code>	42
4.7.5. Define the levels of a Z-axis: <code>zaxisDefLevels</code>	43
4.7.6. Get all levels of a Z-axis: <code>zaxisInqLevels</code>	43
4.7.7. Get one level of a Z-axis: <code>zaxisInqLevel</code>	43
4.8. T-axis functions	44
4.8.1. Create a Time axis: <code>taxisCreate</code>	44
4.8.2. Destroy a Time axis: <code>taxisDestroy</code>	45
4.8.3. Define the reference date: <code>taxisDefRdate</code>	45
4.8.4. Get the reference date: <code>taxisInqRdate</code>	45
4.8.5. Define the reference time: <code>taxisDefRtime</code>	45
4.8.6. Get the reference time: <code>taxisInqRtime</code>	45
4.8.7. Define the verification date: <code>taxisDefVdate</code>	46
4.8.8. Get the verification date: <code>taxisInqVdate</code>	46
4.8.9. Define the verification time: <code>taxisDefVtime</code>	46
4.8.10. Get the verification time: <code>taxisInqVtime</code>	46
4.8.11. Define the calendar: <code>taxisDefCalendar</code>	46
4.8.12. Get the calendar: <code>taxisInqCalendar</code>	47
A. Quick Reference	49
B. Examples	61
B.1. Write a dataset	61
B.1.1. Result	62
B.2. Read a dataset	63
B.3. Copy a dataset	64
C. Environment Variables	67
Index	68

1. Introduction

CDI is an Interface to access Climate and forecast model Data. The interface is independent from a specific data format and has a C and Fortran API. **CDI** was developed for a fast and machine independent access to GRIB and NetCDF datasets with the same interface. The local [MPI-MET](#) data formats SERVICE, EXTRA and IEG are also supported.

1.1. Building from sources

This section describes how to build the **CDI** library from the sources on a UNIX system. **CDI** is using the GNU configure and build system to compile the source code. The only requirement is a working ANSI C99 compiler.

First go to the [download](#) page (<https://code.mpimet.mpg.de/projects/cdi/files>) to get the latest distribution, if you do not already have it.

To take full advantage of **CDI**'s features the following additional libraries should be installed:

- Unidata [NetCDF](#) library (<http://www.unidata.ucar.edu/packages/netcdf>) version 3 or higher. This is needed to read/write NetCDF files with **CDI**.
- ECMWF [ecCodes](#) library (<https://software.ecmwf.int/wiki/display/ECC/ecCodes+Home>) version 2.3.0 or higher. This library is needed to encode/decode GRIB2 records with **CDI**.

1.1.1. Compilation

Compilation is now done by performing the following steps:

1. Unpack the archive, if you haven't already done that:

```
gunzip cdi-$VERSION.tar.gz      # uncompress the archive
tar xf cdi-$VERSION.tar         # unpack it
cd cdi-$VERSION
```

2. Run the configure script:

```
./configure
```

Or optionally with NetCDF support:

```
./configure --with-netcdf=<NetCDF root directory>
```

For an overview of other configuration options use

```
./configure --help
```

3. Compile the program by running make:

```
make
```

The software should compile without problems and the **CDI** library (`libcdi.a`) should be available in the `src` directory of the distribution.

1.1.2. Installation

After the compilation of the source code do a `make install`, possibly as root if the destination permissions require that.

```
make install
```

The library is installed into the directory `<prefix>/lib`. The C and Fortran include files are installed into the directory `<prefix>/include`. `<prefix>` defaults to `/usr/local` but can be changed with the `--prefix` option of the configure script.

2. File Formats

2.1. GRIB

GRIB [\[GRIB\]](#) (GRIdded Binary) is a standard format designed by the World Meteorological Organization (WMO) to support the efficient transmission and storage of gridded meteorological data.

A GRIB record consists of a series of header sections, followed by a bitstream of packed data representing one horizontal grid of data values. The header sections are intended to fully describe the data included in the bitstream, specifying information such as the parameter, units, and precision of the data, the grid system and level type on which the data is provided, and the date and time for which the data are valid.

Non-numeric descriptors are enumerated in tables, such that a 1-byte code in a header section refers to a unique description. The WMO provides a standard set of enumerated parameter names and level types, but the standard also allows for the definition of locally used parameters and geometries. Any activity that generates and distributes GRIB records must also make their locally defined GRIB tables available to users.

The GRIB records must be sorted by time to be able to read them correctly with **CDI**.

CDI does not support the full GRIB standard. The following data representation and level types are implemented:

GRIB1 grid type	GRIB2 template	GRIB_API name	description
0	3.0	regular_ll	Regular longitude/latitude grid
3	–	lambert	Lambert conformal grid
4	3.40	regular_gg	Regular Gaussian longitude/latitude grid
4	3.40	reduced_gg	Reduced Gaussian longitude/latitude grid
10	3.1	rotated_ll	Rotated longitude/latitude grid
50	3.50	sh	Spherical harmonic coefficients
192	3.100	–	Icosahedral-hexagonal GME grid
–	3.101	–	General unstructured grid

GRIB1 level type	GRIB2 level type	GRIB_API name	description
1	1	surface	Surface level
2	2	cloudBase	Cloud base level
3	3	cloudTop	Level of cloud tops
4	4	isothermZero	Level of 0° C isotherm
8	8	nominalTop	Norminal top of atmosphere
9	9	seaBottom	Sea bottom
10	10	entireAtmosphere	Entire atmosphere
100	100	isobaricInhPa	Isobaric level in hPa
102	101	meanSea	Mean sea level
103	102	heightAboveSea	Altitude above mean sea level
105	103	heightAboveGround	Height level above ground
107	104	sigma	Sigma level
109	105	hybrid	Hybrid level
110	105	hybridLayer	Layer between two hybrid levels
111	106	depthBelowLand	Depth below land surface
112	106	depthBelowLandLayer	Layer between two depths below land surface
113	107	theta	Isentropic (theta) level
–	114	–	Snow level
160	160	depthBelowSea	Depth below sea level
162	162	–	Lake or River Bottom
163	163	–	Bottom Of Sediment Layer
164	164	–	Bottom Of Thermally Active Sediment Layer
165	165	–	Bottom Of Sediment Layer Penetrated By Thermal Wave
166	166	–	Mixing Layer
210	–	isobaricInPa	Isobaric level in Pa

2.1.1. GRIB edition 1

GRIB1 is implemented in **CDI** as an internal library and enabled per default. The internal GRIB1 library is called CGRIBEX. This is a lightweight version of the ECMWF GRIBEX library. CGRIBEX is written in ANSI C with a portable Fortran interface. The configure option `--disable-cgribex` will disable the encoding/decoding of GRIB1 records with CGRIBEX.

2.1.2. GRIB edition 2

GRIB2 is available in **CDI** via the ECMWF ecCodes [[ecCodes](#)] library. ecCodes is an external library and not part of **CDI**. To use GRIB2 with **CDI** the ecCodes library must be installed before the configuration of the **CDI** library. Use the configure option `--with-eccodes` to enable GRIB2 support.

The ecCodes library is also used to encode/decode GRIB1 records if the support for the CGRIBEX library is disabled. This feature is not tested regularly and the status is experimental!

A single GRIB2 message can contain multiple fields. This feature is not supported in **CDI**!

2.2. NetCDF

NetCDF [[NetCDF](#)] (Network Common Data Form) is an interface for array-oriented data access and a library that provides an implementation of the interface. The NetCDF library also defines

a machine-independent format for representing scientific data. Together, the interface, library, and format support the creation, access, and sharing of scientific data.

CDI only supports the classic data model of NetCDF and arrays up to 4 dimensions. These dimensions should only be used by the horizontal and vertical grid and the time. The NetCDF attributes should follow the [GDT, COARDS or CF Conventions](#).

NetCDF is an external library and not part of **CDI**. To use NetCDF with **CDI** the NetCDF library must be installed before the configuration of the **CDI** library. Use the configure option `--with-netcdf` to enable NetCDF support (see [Build](#)).

2.3. SERVICE

SERVICE is the binary exchange format of the atmospheric general circulation model ECHAM [\[ECHAM\]](#). It has a header section with 8 integer values followed by the data section. The header and the data section have the standard Fortran blocking for binary data records. A SERVICE record can have an accuracy of 4 or 8 bytes and the byteorder can be little or big endian. In **CDI** the accuracy of the header and data section must be the same. The following Fortran code example can be used to read a SERVICE record with an accuracy of 4 bytes:

```
INTEGER*4 icode,ilevel,ideate,itime,nlon,nlat,idispo1,idispo2
REAL*4 field(mlon,mlat)
...
READ(unit) icode,ilevel,ideate,itime,nlon,nlat,idispo1,idispo2
READ(unit) ((field(ilon,ilat), ilon=1,nlon), ilat=1,nlat)
```

The constants `mlon` and `mlat` must be greater or equal than `nlon` and `nlat`. The meaning of the variables are:

<code>icode</code>	The code number
<code>ilevel</code>	The level
<code>ideate</code>	The date as YYYYMMDD
<code>itime</code>	The time as hhmmss
<code>nlon</code>	The number of longitudes
<code>nlat</code>	The number of latitudes
<code>idispo1</code>	For the users disposal (Not used in CDI)
<code>idispo2</code>	For the users disposal (Not used in CDI)

SERVICE is implemented in **CDI** as an internal library and enabled per default. The configure option `--disable-service` will disable the support for the SERVICE format.

2.4. EXTRA

EXTRA is the standard binary output format of the ocean model MPIOM [\[MPIOM\]](#). It has a header section with 4 integer values followed by the data section. The header and the data section have the standard Fortran blocking for binary data records. An EXTRA record can have an accuracy of 4 or 8 bytes and the byteorder can be little or big endian. In **CDI** the accuracy of the header and data section must be the same. The following Fortran code example can be used to read an EXTRA record with an accuracy of 4 bytes:

```
INTEGER*4 ideate,icode,ilevel,nsiz
REAL*4 field(msize)
...
READ(unit) ideate,icode,ilevel,nsiz
READ(unit) (field(isize),isize=1,nsiz)
```

The constant `msize` must be greater or equal than `nsize`. The meaning of the variables are:

<code>idate</code>	The date as YYYYMMDD
<code>icode</code>	The code number
<code>ilevel</code>	The level
<code>nsize</code>	The size of the field

EXTRA is implemented in **CDI** as an internal library and enabled per default. The configure option `--disable-extra` will disable the support for the EXTRA format.

2.5. IEG

IEG is the standard binary output format of the regional model REMO [[REMO](#)]. It is simple an unpacked GRIB edition 1 format. The product and grid description sections are coded with 4 byte integer values and the data section can have 4 or 8 byte IEEE floating point values. The header and the data section have the standard Fortran blocking for binary data records. The IEG format has a fixed size of 100 for the vertical coordinate table. That means it is not possible to store more than 50 model levels with this format. **CDI** supports only data on Gaussian and LonLat grids for the IEG format.

IEG is implemented in **CDI** as an internal library and enabled per default. The configure option `--disable-ieg` will disable the support for the IEG format.

3. Use of the CDI Library

This chapter provides templates of common sequences of **CDI** calls needed for common uses. For clarity only the names of routines are used. Declarations and error checking were omitted. Statements that are typically invoked multiple times were indented and ... is used to represent arbitrary sequences of other statements. Full parameter lists are described in later chapters. Complete examples for write, read and copy a dataset with **CDI** can be found in [Appendix B](#).

3.1. Creating a dataset

Here is a typical sequence of **CDI** calls used to create a new dataset:

```
gridCreate      ! create a horizontal Grid: from type and size
...
zaxisCreate     ! create a vertical Z-axis: from type and size
...
taxisCreate     ! create a Time axis: from type
...
vlistCreate     ! create a variable list
...
    vlistDefVar  ! define variables: from Grid and Z-axis
...
streamOpenWrite ! create a dataset: from name and file type
...
streamDefVlist  ! define variable list
...
streamDefTimestep ! define time step
...
    streamWriteVar ! write variable
...
streamClose     ! close the dataset
...
vlistDestroy    ! destroy the variable list
...
taxisDestroy    ! destroy the Time axis
...
zaxisDestroy    ! destroy the Z-axis
...
gridDestroy     ! destroy the Grid
```

3.2. Reading a dataset

Here is a typical sequence of **CDI** calls used to read a dataset:

```
streamOpenRead  ! open existing dataset
...
streamInqVlist  ! find out what is in it
...
    vlistInqVarGrid ! get an identifier to the Grid
...
```

```

    vlistInqVarZaxis ! get an identifier to the Z-axis
    ...
    vlistInqTaxis    ! get an identifier to the T-axis
    ...
    streamInqTimestep ! get time step
    ...
    streamReadVar     ! read variable
    ...
    streamClose       ! close the dataset

```

3.3. Compiling and Linking with the CDI library

Details of how to compile and link a program that uses the **CDI** C or FORTRAN interfaces differ, depending on the operating system, the available compilers, and where the **CDI** library and include files are installed. Here are examples of how to compile and link a program that uses the **CDI** library on a Unix platform, so that you can adjust these examples to fit your installation. Every C file that references **CDI** functions or constants must contain an appropriate `include` statement before the first such reference:

```
#include "cdi.h"
```

Unless the `cdi.h` file is installed in a standard directory where C compiler always looks, you must use the `-I` option when invoking the compiler, to specify a directory where `cdi.h` is installed, for example:

```
cc -c -I/usr/local/cdi/include myprogram.c
```

Alternatively, you could specify an absolute path name in the `include` statement, but then your program would not compile on another platform where **CDI** is installed in a different location. Unless the **CDI** library is installed in a standard directory where the linker always looks, you must use the `-L` and `-l` options to link an object file that uses the **CDI** library. For example:

```
cc -o myprogram myprogram.o -L/usr/local/cdi/lib -lcdi -lm
```

Alternatively, you could specify an absolute path name for the library:

```
cc -o myprogram myprogram.o -L/usr/local/cdi/lib/libcdi -lm
```

If the **CDI** library is using other external libraries, you must add this libraries in the same way. For example with the NetCDF library:

```
cc -o myprogram myprogram.o -L/usr/local/cdi/lib -lcdi -lm \
    -L/usr/local/netcdf/lib -lnetcdf
```

4. CDI modules

4.1. Dataset functions

This module contains functions to read and write the data. To create a new dataset the output format must be specified with one of the following predefined file format types:

<code>CDI_FILETYPE_GRB</code>	File type GRIB version 1
<code>CDI_FILETYPE_GRB2</code>	File type GRIB version 2
<code>CDI_FILETYPE_NC</code>	File type NetCDF
<code>CDI_FILETYPE_NC2</code>	File type NetCDF version 2 (64-bit offset)
<code>CDI_FILETYPE_NC4</code>	File type NetCDF-4 (HDF5)
<code>CDI_FILETYPE_NC4C</code>	File type NetCDF-4 classic
<code>CDI_FILETYPE_NC5</code>	File type NetCDF version 5 (64-bit data)
<code>CDI_FILETYPE_NCZARR</code>	File type NetCDF NCZarr
<code>CDI_FILETYPE_SRV</code>	File type SERVICE
<code>CDI_FILETYPE_EXT</code>	File type EXTRA
<code>CDI_FILETYPE_IEG</code>	File type IEG

`CDI_FILETYPE_GRB2` is only available if the **CDI** library was compiled with ecCodes support and all NetCDF file types are only available if the **CDI** library was compiled with NetCDF support! To set the byte order of a binary dataset with the file format type `CDI_FILETYPE_SRV`, `CDI_FILETYPE_EXT` or `CDI_FILETYPE_IEG` use one of the following predefined constants in the call to [streamDefByteorder](#):

<code>CDI_BIGENDIAN</code>	Byte order big endian
<code>CDI_LITTLEENDIAN</code>	Byte order little endian

4.1.1. Create a new dataset: `streamOpenWrite`

The function `streamOpenWrite` creates a new dataset.

Usage

```
int streamOpenWrite(const char *path, int filetype);
```

path The name of the new dataset.

filetype The type of the file format, one of the set of predefined **CDI** file format types. The valid **CDI** file format types are `CDI_FILETYPE_GRB`, `CDI_FILETYPE_GRB2`, `CDI_FILETYPE_NC`, `CDI_FILETYPE_NC2`, `CDI_FILETYPE_NC4`, `CDI_FILETYPE_NC4C`, `CDI_FILETYPE_NC5`, `CDI_FILETYPE_NCZARR`, `CDI_FILETYPE_SRV`, `CDI_FILETYPE_EXT` and `CDI_FILETYPE_IEG`.

Result

Upon successful completion `streamOpenWrite` returns an identifier to the open stream. Otherwise, a negative number with the error status is returned.

Errors

CDI_ESYSTEM	Operating system error.
CDI_EINVAL	Invalid argument.
CDI_EUFILETYPE	Unsupported file type.
CDI_ELIBNAVAIL	Library support not compiled in.

Example

Here is an example using `streamOpenWrite` to create a new NetCDF file named `foo.nc` for writing:

```
#include "cdi.h"
...
int streamID;
...
streamID = streamOpenWrite("foo.nc", CDI_FILETYPE_NC);
if ( streamID < 0 ) handle_error(streamID);
...
```

4.1.2. Open a dataset for reading: `streamOpenRead`

The function `streamOpenRead` opens an existing dataset for reading.

Usage

```
int streamOpenRead(const char *path);
```

`path` The name of the dataset to be read.

Result

Upon successful completion `streamOpenRead` returns an identifier to the open stream. Otherwise, a negative number with the error status is returned.

Errors

CDI_ESYSTEM	Operating system error.
CDI_EINVAL	Invalid argument.
CDI_EUFILETYPE	Unsupported file type.
CDI_ELIBNAVAIL	Library support not compiled in.

Example

Here is an example using `streamOpenRead` to open an existing NetCDF file named `foo.nc` for reading:

```
#include "cdi.h"
...
int streamID;
...
streamID = streamOpenRead("foo.nc");
if ( streamID < 0 ) handle_error(streamID);
...
```

4.1.3. Close an open dataset: `streamClose`

The function `streamClose` closes an open dataset.

Usage

```
void streamClose(int streamID);
```

`streamID` Stream ID, from a previous call to [streamOpenRead](#) or [streamOpenWrite](#).

4.1.4. Get the filetype: `streamInqFiletype`

The function `streamInqFiletype` returns the filetype of a stream.

Usage

```
int streamInqFiletype(int streamID);
```

`streamID` Stream ID, from a previous call to [streamOpenRead](#) or [streamOpenWrite](#).

Result

`streamInqFiletype` returns the type of the file format, one of the set of predefined **CDI** file format types. The valid **CDI** file format types are `CDI_FILETYPE_GRB`, `CDI_FILETYPE_GRB2`, `CDI_FILETYPE_NC`, `CDI_FILETYPE_NC2`, `CDI_FILETYPE_NC4`, `CDI_FILETYPE_NC4C`, `CDI_FILETYPE_NC5`, `CDI_FILETYPE_NCXARR`, `CDI_FILETYPE_SRV`, `CDI_FILETYPE_EXT` and `CDI_FILETYPE_IEG`.

4.1.5. Define the byte order: `streamDefByteorder`

The function `streamDefByteorder` defines the byte order of a binary dataset with the file format type `CDI_FILETYPE_SRV`, `CDI_FILETYPE_EXT` or `CDI_FILETYPE_IEG`.

Usage

```
void streamDefByteorder(int streamID, int byteorder);
```

`streamID` Stream ID, from a previous call to [streamOpenWrite](#).

`byteorder` The byte order of a dataset, one of the **CDI** constants `CDI_BIGENDIAN` and `CDI_LITTLEENDIAN`.

4.1.6. Get the byte order: `streamInqByteorder`

The function `streamInqByteorder` returns the byte order of a binary dataset with the file format type `CDI_FILETYPE_SRV`, `CDI_FILETYPE_EXT` or `CDI_FILETYPE_IEG`.

Usage

```
int streamInqByteorder(int streamID);
```

`streamID` Stream ID, from a previous call to [streamOpenRead](#) or [streamOpenWrite](#).

Result

`streamInqByteorder` returns the type of the byte order. The valid **CDI** byte order types are `CDI_BIGENDIAN` and `CDI_LITTLEENDIAN`

4.1.7. Define the variable list: `streamDefVlist`

The function `streamDefVlist` defines the variable list of a stream.

To safeguard against errors by modifying the wrong vlist object, this function makes the passed vlist object immutable. All further vlist changes have to use the vlist object returned by `streamInqVlist()`.

Usage

```
void streamDefVlist(int streamID, int vlistID);
```

`streamID` Stream ID, from a previous call to `streamOpenWrite`.

`vlistID` Variable list ID, from a previous call to `vlistCreate`.

4.1.8. Get the variable list: `streamInqVlist`

The function `streamInqVlist` returns the variable list of a stream.

Usage

```
int streamInqVlist(int streamID);
```

`streamID` Stream ID, from a previous call to `streamOpenRead` or `streamOpenWrite`.

Result

`streamInqVlist` returns an identifier to the variable list.

4.1.9. Define a timestep: `streamDefTimestep`

The function `streamDefTimestep` defines a timestep of a stream by the identifier `tsID`. The identifier `tsID` is the timestep index starting at 0 for the first timestep. Before calling this function the functions `taxisDefVdate` and `taxisDefVtime` should be used to define the timestamp for this timestep. All calls to write the data refer to this timestep.

Usage

```
int streamDefTimestep(int streamID, int tsID);
```

`streamID` Stream ID, from a previous call to `streamOpenWrite`.

`tsID` Timestep identifier.

Result

`streamDefTimestep` returns the number of expected records of the timestep.

4.1.10. Get timestep information: `streamInqTimestep`

The function `streamInqTimestep` sets the next timestep to the identifier `tsID`. The identifier `tsID` is the timestep index starting at 0 for the first timestep. After a call to this function the functions `taxisInqVdate` and `taxisInqVtime` can be used to read the timestamp for this timestep. All calls to read the data refer to this timestep.

Usage

```
int streamInqTimestep(int streamID, int tsID);
```

`streamID` Stream ID, from a previous call to [streamOpenRead](#) or [streamOpenWrite](#).
`tsID` Timestep identifier.

Result

`streamInqTimestep` returns the number of records of the timestep or 0, if the end of the file is reached.

4.1.11. Write a variable: streamWriteVar

The function `streamWriteVar` writes the values of one time step of a variable to an open dataset. The values are converted to the external data type of the variable, if necessary.

Usage

```
void streamWriteVar(int streamID, int varID, const double *data, SizeType nmiss);
```

`streamID` Stream ID, from a previous call to [streamOpenWrite](#).
`varID` Variable identifier.
`data` Pointer to a block of double precision floating point data values to be written.
`nmiss` Number of missing values.

4.1.12. Write a variable: streamWriteVarF

The function `streamWriteVarF` writes the values of one time step of a variable to an open dataset. The values are converted to the external data type of the variable, if necessary.

Usage

```
void streamWriteVarF(int streamID, int varID, const float *data, SizeType nmiss);
```

`streamID` Stream ID, from a previous call to [streamOpenWrite](#).
`varID` Variable identifier.
`data` Pointer to a block of single precision floating point data values to be written.
`nmiss` Number of missing values.

4.1.13. Write a horizontal slice of a variable: streamWriteVarSlice

The function `streamWriteVarSlice` writes the values of a horizontal slice of a variable to an open dataset. The values are converted to the external data type of the variable, if necessary.

Usage

```
void streamWriteVarSlice(int streamID, int varID, int levelID, const double *data,
                        SizeType nmiss);
```

`streamID` Stream ID, from a previous call to [streamOpenWrite](#).
`varID` Variable identifier.
`levelID` Level identifier.
`data` Pointer to a block of double precision floating point data values to be written.
`nmiss` Number of missing values.

4.1.14. Write a horizontal slice of a variable: streamWriteVarSliceF

The function `streamWriteVarSliceF` writes the values of a horizontal slice of a variable to an open dataset. The values are converted to the external data type of the variable, if necessary.

Usage

```
void streamWriteVarSliceF(int streamID, int varID, int levelID, const float *data,
                          SizeType nmiss);
```

`streamID` Stream ID, from a previous call to `streamOpenWrite`.

`varID` Variable identifier.

`levelID` Level identifier.

`data` Pointer to a block of single precision floating point data values to be written.

`nmiss` Number of missing values.

4.1.15. Read a variable: streamReadVar

The function `streamReadVar` reads all the values of one time step of a variable from an open dataset.

Usage

```
void streamReadVar(int streamID, int varID, double *data, SizeType *nmiss);
```

`streamID` Stream ID, from a previous call to `streamOpenRead`.

`varID` Variable identifier.

`data` Pointer to the location into which the data values are read. The caller must allocate space for the returned values.

`nmiss` Number of missing values.

4.1.16. Read a variable: streamReadVarF

The function `streamReadVar` reads all the values of one time step of a variable from an open dataset.

Usage

```
void streamReadVar(int streamID, int varID, float *data, SizeType *nmiss);
```

`streamID` Stream ID, from a previous call to `streamOpenRead`.

`varID` Variable identifier.

`data` Pointer to the location into which the data values are read. The caller must allocate space for the returned values.

`nmiss` Number of missing values.

4.1.17. Read a horizontal slice of a variable: streamReadVarSlice

The function `streamReadVarSlice` reads all the values of a horizontal slice of a variable from an open dataset.

Usage

```
void streamReadVarSlice(int streamID, int varID, int levelID, double *data,  
                       .SizeType *nmiss);
```

streamID Stream ID, from a previous call to [streamOpenRead](#).

varID Variable identifier.

levelID Level identifier.

data Pointer to the location into which the data values are read. The caller must allocate space for the returned values.

nmiss Number of missing values.

4.1.18. Read a horizontal slice of a variable: streamReadVarSliceF

The function `streamReadVarSliceF` reads all the values of a horizontal slice of a variable from an open dataset.

Usage

```
void streamReadVarSliceF(int streamID, int varID, int levelID, float *data,  
                       .SizeType *nmiss);
```

streamID Stream ID, from a previous call to [streamOpenRead](#).

varID Variable identifier.

levelID Level identifier.

data Pointer to the location into which the data values are read. The caller must allocate space for the returned values.

nmiss Number of missing values.

4.2. Variable list functions

This module contains functions to handle a list of variables. A variable list is a collection of all variables of a dataset.

4.2.1. Create a variable list: `vlistCreate`

Usage

```
int vlistCreate(void);
```

Example

Here is an example using `vlistCreate` to create a variable list and add a variable with `vlistDefVar`.

```
#include "cdi.h"
...
int vlistID, varID;
...
vlistID = vlistCreate();
varID = vlistDefVar(vlistID, gridID, zaxisID, TIME_VARYING);
...
streamDefVlist(streamID, vlistID);
...
vlistDestroy(vlistID);
...
```

4.2.2. Destroy a variable list: `vlistDestroy`

Usage

```
void vlistDestroy(int vlistID);
```

`vlistID` Variable list ID, from a previous call to `vlistCreate`.

4.2.3. Copy a variable list: `vlistCopy`

The function `vlistCopy` copies all entries from `vlistID1` to `vlistID2`.

Usage

```
void vlistCopy(int vlistID2, int vlistID1);
```

`vlistID2` Target variable list ID.

`vlistID1` Source variable list ID.

4.2.4. Duplicate a variable list: `vlistDuplicate`

The function `vlistDuplicate` duplicates the variable list from `vlistID1`.

Usage

```
int vlistDuplicate(int vlistID);
```

`vlistID` Variable list ID, from a previous call to `vlistCreate` or `streamInqVlist`.

Result

`vlistDuplicate` returns an identifier to the duplicated variable list.

4.2.5. Concatenate two variable lists: `vlistCat`

Concatenate the variable list `vlistID1` at the end of `vlistID2`.

Usage

```
void vlistCat(int vlistID2, int vlistID1);
```

`vlistID2` Target variable list ID.

`vlistID1` Source variable list ID.

4.2.6. Copy some entries of a variable list: `vlistCopyFlag`

The function `vlistCopyFlag` copies all entries with a flag from `vlistID1` to `vlistID2`.

Usage

```
void vlistCopyFlag(int vlistID2, int vlistID1);
```

`vlistID2` Target variable list ID.

`vlistID1` Source variable list ID.

4.2.7. Number of variables in a variable list: `vlistNvars`

The function `vlistNvars` returns the number of variables in the variable list `vlistID`.

Usage

```
int vlistNvars(int vlistID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

Result

`vlistNvars` returns the number of variables in a variable list.

4.2.8. Number of grids in a variable list: `vlistNgrids`

The function `vlistNgrids` returns the number of grids in the variable list `vlistID`.

Usage

```
int vlistNgrids(int vlistID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

Result

`vlistNgrids` returns the number of grids in a variable list.

4.2.9. Number of zaxis in a variable list: `vlistNzaxis`

The function `vlistNzaxis` returns the number of zaxis in the variable list `vlistID`.

Usage

```
int vlistNzaxis(int vlistID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

Result

`vlistNzaxis` returns the number of zaxis in a variable list.

4.2.10. Define the time axis: vlistDefTaxis

The function `vlistDefTaxis` defines the time axis of a variable list.

Usage

```
void vlistDefTaxis(int vlistID, int taxisID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#).

`taxisID` Time axis ID, from a previous call to [taxisCreate](#).

4.2.11. Get the time axis: vlistInqTaxis

The function `vlistInqTaxis` returns the time axis of a variable list.

Usage

```
int vlistInqTaxis(int vlistID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

Result

`vlistInqTaxis` returns an identifier to the time axis.

4.3. Variable functions

This module contains functions to add new variables to a variable list and to get information about variables from a variable list. To add new variables to a variables list one of the following timestep types must be specified:

TSTEP_CONSTANT	The data values have no time dimension.
TSTEP_INSTANT	The data values are representative of points in space or time (instantaneous).
TSTEP_ACCUM	The data values are representative of a sum or accumulation over the cell.
TSTEP_AVG	Mean (average value)
TSTEP_MAX	Maximum
TSTEP_MIN	Minimum
TSTEP_SD	Standard deviation

The default data type is 16 bit for GRIB and 32 bit for all other file format types. To change the data type use one of the following predefined constants:

CDI_DATATYPE_PACK8	8 packed bit (only for GRIB)
CDI_DATATYPE_PACK16	16 packed bit (only for GRIB)
CDI_DATATYPE_PACK24	24 packed bit (only for GRIB)
CDI_DATATYPE_FLT32	32 bit floating point
CDI_DATATYPE_FLT64	64 bit floating point
CDI_DATATYPE_INT8	8 bit integer
CDI_DATATYPE_INT16	16 bit integer
CDI_DATATYPE_INT32	32 bit integer

4.3.1. Define a Variable: `vlistDefVar`

The function `vlistDefVar` adds a new variable to `vlistID`.

Usage

```
int vlistDefVar(int vlistID, int gridID, int zaxisID, int timetype);
```

`vlistID` Variable list ID, from a previous call to `vlistCreate`.

`gridID` Grid ID, from a previous call to `gridCreate`.

`zaxisID` Z-axis ID, from a previous call to `zaxisCreate`.

`timetype` One of the set of predefined **CDI** timestep types. The valid **CDI** timestep types are `TIME_CONSTANT` and `TIME_VARYING`.

Result

`vlistDefVar` returns an identifier to the new variable.

Example

Here is an example using `vlistCreate` to create a variable list and add a variable with `vlistDefVar`.

```
#include "cdi.h"
...
```

```
int vlistID, varID;
...
vlistID = vlistCreate();
varID = vlistDefVar(vlistID, gridID, zaxisID, TIME_VARYING);
...
streamDefVlist(streamID, vlistID);
...
vlistDestroy(vlistID);
...
```

4.3.2. Get the Grid ID of a Variable: `vlistInqVarGrid`

The function `vlistInqVarGrid` returns the grid ID of a Variable.

Usage

```
int vlistInqVarGrid(int vlistID, int varID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

`varID` Variable identifier.

Result

`vlistInqVarGrid` returns the grid ID of the Variable.

4.3.3. Get the Zaxis ID of a Variable: `vlistInqVarZaxis`

The function `vlistInqVarZaxis` returns the zaxis ID of a variable.

Usage

```
int vlistInqVarZaxis(int vlistID, int varID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

`varID` Variable identifier.

Result

`vlistInqVarZaxis` returns the zaxis ID of the variable.

4.3.4. Get the timestep type of a Variable: `vlistInqVarTsteptype`

The function `vlistInqVarTsteptype` returns the timestep type of a Variable.

Usage

```
int vlistInqVarTsteptype(int vlistID, int varID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

`varID` Variable identifier.

Result

`vlistInqVarTsteptype` returns the timestep type of the Variable, one of the set of predefined **CDI** timestep types. The valid **CDI** timestep types are `TSTEP_INSTANT`, `TSTEP_ACCUM`, `TSTEP_AVG`, `TSTEP_MAX`, `TSTEP_MIN` and `TSTEP_SD`.

4.3.5. Define the code number of a Variable: `vlistDefVarCode`

The function `vlistDefVarCode` defines the code number of a variable.

Usage

```
void vlistDefVarCode(int vlistID, int varID, int code);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#).

`varID` Variable identifier.

`code` Code number.

4.3.6. Get the Code number of a Variable: `vlistInqVarCode`

The function `vlistInqVarCode` returns the code number of a variable.

Usage

```
int vlistInqVarCode(int vlistID, int varID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

`varID` Variable identifier.

Result

`vlistInqVarCode` returns the code number of the variable.

4.3.7. Define the data type of a Variable: `vlistDefVarDatatype`

The function `vlistDefVarDatatype` defines the data type of a variable.

Usage

```
void vlistDefVarDatatype(int vlistID, int varID, int datatype);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#).

`varID` Variable identifier.

`datatype` The data type identifier. The valid **CDI** data types are `CDI_DATATYPE_PACK8`, `CDI_DATATYPE_PACK16`, `CDI_DATATYPE_PACK24`, `CDI_DATATYPE_FLT32`, `CDI_DATATYPE_FLT64`, `CDI_DATATYPE_INT8`, `CDI_DATATYPE_INT16` and `CDI_DATATYPE_INT32`.

4.3.8. Get the data type of a Variable: `vlistInqVarDatatype`

The function `vlistInqVarDatatype` returns the data type of a variable.

Usage

```
int vlistInqVarDatatype(int vlistID, int varID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

`varID` Variable identifier.

Result

`vlistInqVarDatatype` returns an identifier to the data type of the variable. The valid **CDI** data types are `CDI_DATATYPE_PACK8`, `CDI_DATATYPE_PACK16`, `CDI_DATATYPE_PACK24`, `CDI_DATATYPE_FLT32`, `CDI_DATATYPE_FLT64`, `CDI_DATATYPE_INT8`, `CDI_DATATYPE_INT16` and `CDI_DATATYPE_INT32`.

4.3.9. Define the missing value of a Variable: `vlistDefVarMissval`

The function `vlistDefVarMissval` defines the missing value of a variable.

Usage

```
void vlistDefVarMissval(int vlistID, int varID, double missval);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#).

`varID` Variable identifier.

`missval` Missing value.

4.3.10. Get the missing value of a Variable: `vlistInqVarMissval`

The function `vlistInqVarMissval` returns the missing value of a variable.

Usage

```
double vlistInqVarMissval(int vlistID, int varID);
```

`vlistID` Variable list ID, from a previous call to [vlistCreate](#) or [streamInqVlist](#).

`varID` Variable identifier.

Result

`vlistInqVarMissval` returns the missing value of the variable.

4.4. Key attributes

Attributes are metadata used to describe variables or a data set. CDI distinguishes between key attributes and user attributes. User defined attributes are described in the next chapter.

Key attributes are attributes that are interpreted by CDI. An example is the name or the units of a variable.

Key attributes can be defined for data variables and coordinate variables. Use the variable ID or one of the following identifiers for the coordinates:

CDI_XAXIS	X-axis ID
CDI_YAXIS	Y-axis ID
CDI_GLOBAL	Global Z-axis

Some keys like name and units can be used for all variables. Other keys are very special and should only be used for certain variables. The user is also responsible for the data type of the key. CDI supports string, integer, floating point and byte array key attributes. The following key attributes are available:

String keys

CDI_KEY_NAME	Variable name
CDI_KEY_LONGNAME	Long name of the variable
CDI_KEY_STDNAME	CF Standard name of the variable
CDI_KEY_UNITS	Units of the variable
CDI_KEY_REFERENCEURI	Reference URI to grid file

Integer keys

CDI_KEY_NUMBEROFGRIDUSED	GRIB2 numberOfGridUsed
CDI_KEY_NUMBEROFGRIDINREFERENCE	GRIB2 numberOfGridInReference
CDI_KEY_NUMBEROFVGRIDUSED	GRIB2 numberOfVGridUsed
CDI_KEY_NLEV	GRIB2 nlev
CDI_KEY_CHUNKTYPE	ChunkType: CDI_CHUNK_AUTO/CDI_CHUNK_GRID/CDI_CHUNK_...
CDI_KEY_CHUNKSIZE	ChunkSize

Floating point keys

CDI_KEY_MISSVAL	Missing value
-----------------	---------------

Byte array keys

CDI_KEY_UUID	UUID for grid/Z-axis reference [size: CDI_UUID_SIZE]
--------------	--

4.4.1. Define a string from a key: `cdiDefKeyString`

The function `cdiDefKeyString` defines a text string from a key.

Usage

```
int cdiDefKeyString(int cdiID, int varID, int key, const char *string);
```

cdiID CDI object ID (vlistID, gridID, zaxisID).
varID Variable identifier or CDI_GLOBAL.
key The key to be searched.
string The address of a string where the data will be read.

Result

`cdiDefKeyString` returns `CDI_NOERR` if OK.

Example

Here is an example using `cdiDefKeyString` to define the name of a variable:

```
#include "cdi.h"
...
int vlistID, varID, status;
...
vlistID = vlistCreate();
varID = vlistDefVar(vlistID, gridID, zaxisID, TIME_VARYING);
...
status = cdiDefKeyString(vlistID, varID, CDI_KEY_NAME, "temperature");
...
```

4.4.2. Get a string from a key: `cdiInqKeyString`

The function `cdiInqKeyString` gets a text string from a key.

Usage

```
int cdiInqKeyString(int cdiID, int varID, int key, char *string, int *length);
```

cdiID CDI object ID (vlistID, gridID, zaxisID).
varID Variable identifier or CDI_GLOBAL.
key The key to be searched.
string The address of a string where the data will be retrieved. The caller must allocate space for the returned string.
length The allocated length of the string on input.

Result

`cdiInqKeyString` returns `CDI_NOERR` if key is available.

Example

Here is an example using `cdiInqKeyString` to get the name of the first variable:

```
#include "cdi.h"
...
#define STRLEN 256
...
int streamID, vlistID, varID, status;
int length = STRLEN;
char name[STRLEN];
```

```
...
streamID = streamOpenRead(...);
vlistID = streamInqVlist(streamID);
...
varID = 0;
status = cdiInqKeyString(vlistID, varID, CDI_KEY_NAME, name, &length);
...
```

4.4.3. Define an integer value from a key: `cdiDefKeyInt`

The function `cdiDefKeyInt` defines an integer value from a key.

Usage

```
int cdiDefKeyInt(int cdiID, int varID, int key, int value);
```

`cdiID` CDI object ID (vlistID, gridID, zaxisID).
`varID` Variable identifier or `CDI_GLOBAL`.
`key` The key to be searched.
`value` An integer where the data will be read.

Result

`cdiDefKeyInt` returns `CDI_NOERR` if OK.

4.4.4. Get an integer value from a key: `cdiInqKeyInt`

The function `cdiInqKeyInt` gets an integer value from a key.

Usage

```
int cdiInqKeyInt(int cdiID, int varID, int key, int *value);
```

`cdiID` CDI object ID (vlistID, gridID, zaxisID).
`varID` Variable identifier or `CDI_GLOBAL`.
`key` The key to be searched..
`value` The address of an integer where the data will be retrieved.

Result

`cdiInqKeyInt` returns `CDI_NOERR` if key is available.

4.4.5. Define a floating point value from a key: `cdiDefKeyFloat`

The function `cdiDefKeyFloat` defines a **CDI** floating point value from a key.

Usage

```
int cdiDefKeyFloat(int cdiID, int varID, int key, double value);
```

`cdiID` CDI object ID (vlistID, gridID, zaxisID).
`varID` Variable identifier or `CDI_GLOBAL`.
`key` The key to be searched
`value` A double where the data will be read

Result

`cdiDefKeyFloat` returns `CDLNOERR` if OK.

4.4.6. Get a floating point value from a key: `cdiInqKeyFloat`

The function `cdiInqKeyFloat` gets a floating point value from a key.

Usage

```
int cdiInqKeyFloat(int cdiID, int varID, int key, double *value);
```

`cdiID` CDI object ID (`vlistID`, `gridID`, `zaxisID`).

`varID` Variable identifier or `CDLGLOBAL`.

`key` The key to be searched.

`value` The address of a double where the data will be retrieved.

Result

`cdiInqKeyFloat` returns `CDLNOERR` if key is available.

4.4.7. Define a byte array from a key: `cdiDefKeyBytes`

The function `cdiDefKeyBytes` defines a byte array from a key.

Usage

```
int cdiDefKeyBytes(int cdiID, int varID, int key, const unsigned char *bytes,
                  int length);
```

`cdiID` CDI object ID (`vlistID`, `gridID`, `zaxisID`).

`varID` Variable identifier or `CDLGLOBAL`.

`key` The key to be searched.

`bytes` The address of a byte array where the data will be read.

`length` Length of the byte array

Result

`cdiDefKeyBytes` returns `CDLNOERR` if OK.

4.4.8. Get a byte array from a key: `cdiInqKeyBytes`

The function `cdiInqKeyBytes` gets a byte array from a key.

Usage

```
int cdiInqKeyBytes(int cdiID, int varID, int key, unsigned char *bytes, int *length);
```

`cdiID` CDI object ID (`vlistID`, `gridID`, `zaxisID`).

`varID` Variable identifier or `CDLGLOBAL`.

`key` The key to be searched.

`bytes` The address of a byte array where the data will be retrieved. The caller must allocate space for the returned byte array.

`length` The allocated length of the byte array on input.

Result

`cdiInqKeyBytes` returns `CDI_NOERR` if key is available.

4.5. User attributes

Attributes are metadata used to describe variables or a data set. CDI distinguishes between key attributes and user attributes. Key attributes are described in the last chapter.

User defined attributes are additional attributes that are not interpreted by CDI. These attributes are only available for NetCDF datasets. Here they correspond to all attributes that are not used by CDI as key attributes.

A user defined attribute has a variable to which it is assigned, a name, a type, a length, and a sequence of one or more values. The attributes have to be defined after the variable is created and before the variables list is associated with a stream.

It is also possible to have attributes that are not associated with any variable. These are called global attributes and are identified by using `CDI_GLOBAL` as a variable pseudo-ID. Global attributes are usually related to the dataset as a whole.

CDI supports integer, floating point and text attributes. The data types are defined by the following predefined constants:

<code>CDI_DATATYPE_INT16</code>	16-bit integer attribute
<code>CDI_DATATYPE_INT32</code>	32-bit integer attribute
<code>CDI_DATATYPE_FLT32</code>	32-bit floating point attribute
<code>CDI_DATATYPE_FLT64</code>	64-bit floating point attribute
<code>CDI_DATATYPE_TXT</code>	Text attribute

4.5.1. Get number of attributes: `cdiInqNatts`

The function `cdiInqNatts` gets the number of attributes assigned to this variable.

Usage

```
int cdiInqNatts(int cdiID, int varID, int *nattsp);
```

`cdiID` CDI ID, from a previous call to [vlistCreate](#), [gridCreate](#) or [streamInqVlist](#).
`varID` Variable identifier, or `CDI_GLOBAL` for a global attribute.
`nattsp` Pointer to location for returned number of attributes.

4.5.2. Get information about an attribute: `cdiInqAtt`

The function `cdiInqAtt` gets information about an attribute.

Usage

```
int cdiInqAtt(int cdiID, int varID, int attnum, char *name, int *typep, int *lenp);
```

`cdiID` CDI ID, from a previous call to [vlistCreate](#), [gridCreate](#) or [streamInqVlist](#).
`varID` Variable identifier, or `CDI_GLOBAL` for a global attribute.
`attnum` Attribute number (from 0 to `natts-1`).
`name` Pointer to the location for the returned attribute name. The caller must allocate space for the returned string. The maximum possible length, in characters, of the string is given by the predefined constant `CDI_MAX_NAME`.
`typep` Pointer to location for returned attribute type.
`lenp` Pointer to location for returned attribute number.

4.5.3. Define a text attribute: `cdiDefAttTxt`

The function `cdiDefAttTxt` defines a text attribute.

Usage

```
int cdiDefAttTxt(int cdiID, int varID, const char *name, int len, const char *tp);
```

`cdiID` CDI ID, from a previous call to `vlistCreate`, `gridCreate` or `zaxisCreate`.

`varID` Variable identifier, or `CDI_GLOBAL` for a global attribute.

`name` Attribute name.

`len` Number of values provided for the attribute.

`tp` Pointer to one or more character values.

Example

Here is an example using `cdiDefAttTxt` to define the attribute "description":

```
#include "cdi.h"
...
int vlistID, varID, status;
char text[] = "description-of-the-variable";
...
vlistID = vlistCreate();
varID = vlistDefVar(vlistID, gridID, zaxisID, TIME_VARYING);
...
status = cdiDefAttTxt(vlistID, varID, "description", LEN(text), text);
...
```

4.5.4. Get the value(s) of a text attribute: `cdiInqAttTxt`

The function `cdiInqAttTxt` gets the values(s) of a text attribute.

Usage

```
int cdiInqAttTxt(int cdiID, int varID, const char *name, int mlen, char *tp);
```

`cdiID` CDI ID, from a previous call to `vlistCreate`, `gridCreate` or `zaxisCreate`.

`varID` Variable identifier, or `CDI_GLOBAL` for a global attribute.

`name` Attribute name.

`mlen` Number of allocated values provided for the attribute.

`tp` Pointer location for returned text attribute value(s).

4.5.5. Define an integer attribute: `cdiDefAttInt`

The function `cdiDefAttInt` defines an integer attribute.

Usage

```
int cdiDefAttInt(int cdiID, int varID, const char *name, int type, int len,
                 const int *ip);
```

cdiID CDI ID, from a previous call to [vlistCreate](#), [gridCreate](#) or [zaxisCreate](#).
varID Variable identifier, or `CDI_GLOBAL` for a global attribute.
name Attribute name.
type External data type (`CDI_DATATYPE_INT16` or `CDI_DATATYPE_INT32`).
len Number of values provided for the attribute.
ip Pointer to one or more integer values.

4.5.6. Get the value(s) of an integer attribute: `cdiInqAttInt`

The function `cdiInqAttInt` gets the values(s) of an integer attribute.

Usage

```
int cdiInqAttInt(int cdiID, int varID, const char *name, int mlen, int *ip);
```

cdiID CDI ID, from a previous call to [vlistCreate](#), [gridCreate](#) or [zaxisCreate](#).
varID Variable identifier, or `CDI_GLOBAL` for a global attribute.
name Attribute name.
mlen Number of allocated values provided for the attribute.
ip Pointer location for returned integer attribute value(s).

4.5.7. Define a floating point attribute: `cdiDefAttFlt`

The function `cdiDefAttFlt` defines a floating point attribute.

Usage

```
int cdiDefAttFlt(int cdiID, int varID, const char *name, int type, int len,  
                 const double *dp);
```

cdiID CDI ID, from a previous call to [vlistCreate](#), [gridCreate](#) or [zaxisCreate](#).
varID Variable identifier, or `CDI_GLOBAL` for a global attribute.
name Attribute name.
type External data type (`CDI_DATATYPE_FLT32` or `CDI_DATATYPE_FLT64`).
len Number of values provided for the attribute.
dp Pointer to one or more floating point values.

4.5.8. Get the value(s) of a floating point attribute: `cdiInqAttFlt`

The function `cdiInqAttFlt` gets the values(s) of a floating point attribute.

Usage

```
int cdiInqAttFlt(int cdiID, int varID, const char *name, int mlen, double *dp);
```

cdiID CDI ID, from a previous call to [vlistCreate](#), [gridCreate](#) or [zaxisCreate](#).
varID Variable identifier, or `CDI_GLOBAL` for a global attribute.
name Attribute name.
mlen Number of allocated values provided for the attribute.
dp Pointer location for returned floating point attribute value(s).

4.6. Grid functions

This module contains functions to define a new horizontal Grid and to get information from an existing Grid. A Grid object is necessary to define a variable. The following different Grid types are available:

GRID_GENERIC	Generic user defined grid
GRID_LONLAT	Regular longitude/latitude grid
GRID_GAUSSIAN	Regular Gaussian lon/lat grid
GRID_PROJECTION	Projected coordinates
GRID_SPECTRAL	Spherical harmonic coefficients
GRID_GME	Icosahedral-hexagonal GME grid
GRID_CURVILINEAR	Curvilinear grid
GRID_UNSTRUCTURED	Unstructured grid

4.6.1. Create a horizontal Grid: `gridCreate`

The function `gridCreate` creates a horizontal Grid.

Usage

```
int gridCreate(int gridtype, SizeType size);
```

gridtype The type of the grid, one of the set of predefined **CDI** grid types. The valid **CDI** grid types are `GRID_GENERIC`, `GRID_LONLAT`, `GRID_GAUSSIAN`, `GRID_PROJECTION`, `GRID_SPECTRAL`, `GRID_GME`, `GRID_CURVILINEAR` and `GRID_UNSTRUCTURED`.

size Number of gridpoints.

Result

`gridCreate` returns an identifier to the Grid.

Example

Here is an example using `gridCreate` to create a regular lon/lat Grid:

```
#include "cdi.h"
...
#define nlon 12
#define nlat 6
...
double lons[nlon] = {0, 30, 60, 90, 120, 150, 180, 210, 240, 270, 300, 330};
double lats[nlat] = {-75, -45, -15, 15, 45, 75};
int gridID;
...
gridID = gridCreate(GRID_LONLAT, nlon*nlat);
gridDefXsize(gridID, nlon);
gridDefYsize(gridID, nlat);
gridDefXvals(gridID, lons);
gridDefYvals(gridID, lats);
...
```

4.6.2. Destroy a horizontal Grid: `gridDestroy`

Usage

```
void gridDestroy(int gridID);
```

`gridID` Grid ID, from a previous call to [gridCreate](#).

4.6.3. Duplicate a horizontal Grid: `gridDuplicate`

The function `gridDuplicate` duplicates a horizontal Grid.

Usage

```
int gridDuplicate(int gridID);
```

`gridID` Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

Result

`gridDuplicate` returns an identifier to the duplicated Grid.

4.6.4. Get the type of a Grid: `gridInqType`

The function `gridInqType` returns the type of a Grid.

Usage

```
int gridInqType(int gridID);
```

`gridID` Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

Result

`gridInqType` returns the type of the grid, one of the set of predefined **CDI** grid types. The valid **CDI** grid types are `GRID_GENERIC`, `GRID_LONLAT`, `GRID_GAUSSIAN`, `GRID_PROJECTION`, `GRID_SPECTRAL`, `GRID_GME`, `GRID_CURVILINEAR` and `GRID_UNSTRUCTURED`.

4.6.5. Get the size of a Grid: `gridInqSize`

The function `gridInqSize` returns the size of a Grid.

Usage

```
SizeType gridInqSize(int gridID);
```

`gridID` Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

Result

`gridInqSize` returns the number of grid points of a Grid.

4.6.6. Define the number of values of a X-axis: `gridDefXsize`

The function `gridDefXsize` defines the number of values of a X-axis.

Usage

```
void gridDefXsize(int gridID, SizeType xsize);
```

gridID Grid ID, from a previous call to [gridCreate](#).
xsize Number of values of a X-axis.

4.6.7. Get the number of values of a X-axis: gridInqXsize

The function `gridInqXsize` returns the number of values of a X-axis.

Usage

```
SizeType gridInqXsize(int gridID);
```

gridID Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

Result

`gridInqXsize` returns the number of values of a X-axis.

4.6.8. Define the number of values of a Y-axis: gridDefYsize

The function `gridDefYsize` defines the number of values of a Y-axis.

Usage

```
void gridDefYsize(int gridID, SizeType ysize);
```

gridID Grid ID, from a previous call to [gridCreate](#).
ysize Number of values of a Y-axis.

4.6.9. Get the number of values of a Y-axis: gridInqYsize

The function `gridInqYsize` returns the number of values of a Y-axis.

Usage

```
SizeType gridInqYsize(int gridID);
```

gridID Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

Result

`gridInqYsize` returns the number of values of a Y-axis.

4.6.10. Define the number of parallels between a pole and the equator: gridDefNP

The function `gridDefNP` defines the number of parallels between a pole and the equator of a Gaussian grid.

Usage

```
void gridDefNP(int gridID, int np);
```

gridID Grid ID, from a previous call to [gridCreate](#).
np Number of parallels between a pole and the equator.

4.6.11. Get the number of parallels between a pole and the equator: `gridInqNP`

The function `gridInqNP` returns the number of parallels between a pole and the equator of a Gaussian grid.

Usage

```
int gridInqNP(int gridID);
```

`gridID` Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

Result

`gridInqNP` returns the number of parallels between a pole and the equator.

4.6.12. Define the values of a X-axis: `gridDefXvals`

The function `gridDefXvals` defines all values of the X-axis.

Usage

```
void gridDefXvals(int gridID, const double *xvals);
```

`gridID` Grid ID, from a previous call to [gridCreate](#).

`xvals` X-values of the grid.

4.6.13. Get all values of a X-axis: `gridInqXvals`

The function `gridInqXvals` returns all values of the X-axis.

Usage

```
SizeType gridInqXvals(int gridID, double *xvals);
```

`gridID` Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

`xvals` Pointer to the location into which the X-values are read. The caller must allocate space for the returned values.

Result

Upon successful completion `gridInqXvals` returns the number of values and the values are stored in `xvals`. Otherwise, 0 is returned and `xvals` is empty.

4.6.14. Define the values of a Y-axis: `gridDefYvals`

The function `gridDefYvals` defines all values of the Y-axis.

Usage

```
void gridDefYvals(int gridID, const double *yvals);
```

`gridID` Grid ID, from a previous call to [gridCreate](#).

`yvals` Y-values of the grid.

4.6.15. Get all values of a Y-axis: gridInqYvals

The function `gridInqYvals` returns all values of the Y-axis.

Usage

```
SizeType gridInqYvals(int gridID, double *yvals);
```

`gridID` Grid ID, from a previous call to `gridCreate` or `vlistInqVarGrid`.

`yvals` Pointer to the location into which the Y-values are read. The caller must allocate space for the returned values.

Result

Upon successful completion `gridInqYvals` returns the number of values and the values are stored in `yvals`. Otherwise, 0 is returned and `yvals` is empty.

4.6.16. Define the bounds of a X-axis: gridDefXbounds

The function `gridDefXbounds` defines all bounds of the X-axis.

Usage

```
void gridDefXbounds(int gridID, const double *xbounds);
```

`gridID` Grid ID, from a previous call to `gridCreate`.

`xbounds` X-bounds of the grid.

4.6.17. Get the bounds of a X-axis: gridInqXbounds

The function `gridInqXbounds` returns the bounds of the X-axis.

Usage

```
SizeType gridInqXbounds(int gridID, double *xbounds);
```

`gridID` Grid ID, from a previous call to `gridCreate` or `vlistInqVarGrid`.

`xbounds` Pointer to the location into which the X-bounds are read. The caller must allocate space for the returned values.

Result

Upon successful completion `gridInqXbounds` returns the number of bounds and the bounds are stored in `xbounds`. Otherwise, 0 is returned and `xbounds` is empty.

4.6.18. Define the bounds of a Y-axis: gridDefYbounds

The function `gridDefYbounds` defines all bounds of the Y-axis.

Usage

```
void gridDefYbounds(int gridID, const double *ybounds);
```

`gridID` Grid ID, from a previous call to `gridCreate`.

`ybounds` Y-bounds of the grid.

4.6.19. Get the bounds of a Y-axis: `gridInqYbounds`

The function `gridInqYbounds` returns the bounds of the Y-axis.

Usage

```
SizeType gridInqYbounds(int gridID, double *ybounds);
```

`gridID` Grid ID, from a previous call to [gridCreate](#) or [vlistInqVarGrid](#).

`ybounds` Pointer to the location into which the Y-bounds are read. The caller must allocate space for the returned values.

Result

Upon successful completion `gridInqYbounds` returns the number of bounds and the bounds are stored in `ybounds`. Otherwise, 0 is returned and `ybounds` is empty.

4.7. Z-axis functions

This section contains functions to define a new vertical Z-axis and to get information from an existing Z-axis. A Z-axis object is necessary to define a variable. The following different Z-axis types are available:

ZAXIS_GENERIC	Generic user defined zaxis type
ZAXIS_SURFACE	Surface level
ZAXIS_HYBRID	Hybrid level
ZAXIS_SIGMA	Sigma level
ZAXIS_PRESSURE	Isobaric pressure level in Pascal
ZAXIS_HEIGHT	Height above ground in meters
ZAXIS_ISENTROPIC	Isentropic (theta) level
ZAXIS_ALTITUDE	Altitude above mean sea level in meters
ZAXIS_MEANSEA	Mean sea level
ZAXIS_TOA	Norminal top of atmosphere
ZAXIS_SEA_BOTTOM	Sea bottom
ZAXIS_ATMOSPHERE	Entire atmosphere
ZAXIS_CLOUD_BASE	Cloud base level
ZAXIS_CLOUD_TOP	Level of cloud tops
ZAXIS_ISOTHERM_ZERO	Level of 0° C isotherm
ZAXIS_SNOW	Snow level
ZAXIS_LAKE_BOTTOM	Lake or River Bottom
ZAXIS_SEDIMENT_BOTTOM	Bottom Of Sediment Layer
ZAXIS_SEDIMENT_BOTTOM.TA	Bottom Of Thermally Active Sediment Layer
ZAXIS_SEDIMENT_BOTTOM.TW	Bottom Of Sediment Layer Penetrated By Thermal Wave
ZAXIS_ZAXIS_MIX_LAYER	Mixing Layer
ZAXIS_DEPTH_BELOW_SEA	Depth below sea level in meters
ZAXIS_DEPTH_BELOW_LAND	Depth below land surface in centimeters

4.7.1. Create a vertical Z-axis: `zaxisCreate`

The function `zaxisCreate` creates a vertical Z-axis.

Usage

```
int zaxisCreate(int zaxistype, int size);
```

zaxistype The type of the Z-axis, one of the set of predefined **CDI** Z-axis types. The valid **CDI** Z-axis types are ZAXIS_GENERIC, ZAXIS_SURFACE, ZAXIS_HYBRID, ZAXIS_SIGMA, ZAXIS_PRESSURE, ZAXIS_HEIGHT, ZAXIS_ISENTROPIC, ZAXIS_ALTITUDE, ZAXIS_MEANSEA, ZAXIS_TOA, ZAXIS_SEA_BOTTOM, ZAXIS_ATMOSPHERE, ZAXIS_CLOUD_BASE, ZAXIS_CLOUD_TOP, ZAXIS_ISOTHERM_ZERO, ZAXIS_SNOW, ZAXIS_LAKE_BOTTOM, ZAXIS_SEDIMENT_BOTTOM, ZAXIS_SEDIMENT_BOTTOM.TA, ZAXIS_SEDIMENT_BOTTOM.TW, ZAXIS_MIX_LAYER, ZAXIS_DEPTH_BELOW_SEA and ZAXIS_DEPTH_BELOW_LAND.

size Number of levels.

Result

`zaxisCreate` returns an identifier to the Z-axis.

Example

Here is an example using `zaxisCreate` to create a pressure level Z-axis:

```
#include "cdi.h"
...
#define nlev 5
...
double levs[nlev] = {101300, 92500, 85000, 50000, 20000};
int zaxisID;
...
zaxisID = zaxisCreate(ZAXIS_PRESSURE, nlev);
zaxisDefLevels(zaxisID, levs);
...
```

4.7.2. Destroy a vertical Z-axis: `zaxisDestroy`

Usage

```
void zaxisDestroy(int zaxisID);
```

`zaxisID` Z-axis ID, from a previous call to [zaxisCreate](#).

4.7.3. Get the type of a Z-axis: `zaxisInqType`

The function `zaxisInqType` returns the type of a Z-axis.

Usage

```
int zaxisInqType(int zaxisID);
```

`zaxisID` Z-axis ID, from a previous call to [zaxisCreate](#) or [vlistInqVarZaxis](#).

Result

`zaxisInqType` returns the type of the Z-axis, one of the set of predefined **CDI** Z-axis types. The valid **CDI** Z-axis types are `ZAXIS_GENERIC`, `ZAXIS_SURFACE`, `ZAXIS_HYBRID`, `ZAXIS_SIGMA`, `ZAXIS_PRESSURE`, `ZAXIS_HEIGHT`, `ZAXIS_ISENTROPIC`, `ZAXIS_ALTITUDE`, `ZAXIS_MEANSEA`, `ZAXIS_TOA`, `ZAXIS_SEA_BOTTOM`, `ZAXIS_ATMOSPHERE`, `ZAXIS_CLOUD_BASE`, `ZAXIS_CLOUD_TOP`, `ZAXIS_ISOTHERM_ZERO`, `ZAXIS_SNOW`, `ZAXIS_LAKE_BOTTOM`, `ZAXIS_SEDIMENT_BOTTOM`, `ZAXIS_SEDIMENT_BOTTOM_TA`, `ZAXIS_SEDIMENT_BOTTOM_TL`, `ZAXIS_MIX_LAYER`, `ZAXIS_DEPTH_BELOW_SEA` and `ZAXIS_DEPTH_BELOW_LAND`.

4.7.4. Get the size of a Z-axis: `zaxisInqSize`

The function `zaxisInqSize` returns the size of a Z-axis.

Usage

```
int zaxisInqSize(int zaxisID);
```

`zaxisID` Z-axis ID, from a previous call to [zaxisCreate](#) or [vlistInqVarZaxis](#).

Result

`zaxisInqSize` returns the number of levels of a Z-axis.

4.7.5. Define the levels of a Z-axis: `zaxisDefLevels`

The function `zaxisDefLevels` defines the levels of a Z-axis.

Usage

```
void zaxisDefLevels(int zaxisID, const double *levels);
```

`zaxisID` Z-axis ID, from a previous call to [zaxisCreate](#).

`levels` All levels of the Z-axis.

4.7.6. Get all levels of a Z-axis: `zaxisInqLevels`

The function `zaxisInqLevels` returns all levels of a Z-axis.

Usage

```
void zaxisInqLevels(int zaxisID, double *levels);
```

`zaxisID` Z-axis ID, from a previous call to [zaxisCreate](#) or [vlistInqVarZaxis](#).

`levels` Pointer to the location into which the levels are read. The caller must allocate space for the returned values.

Result

`zaxisInqLevels` saves all levels to the parameter `levels`.

4.7.7. Get one level of a Z-axis: `zaxisInqLevel`

The function `zaxisInqLevel` returns one level of a Z-axis.

Usage

```
double zaxisInqLevel(int zaxisID, int levelID);
```

`zaxisID` Z-axis ID, from a previous call to [zaxisCreate](#) or [vlistInqVarZaxis](#).

`levelID` Level index (range: 0 to `nlevel-1`).

Result

`zaxisInqLevel` returns the level of a Z-axis.

4.8. T-axis functions

This section contains functions to define a new Time axis and to get information from an existing T-axis. A T-axis object is necessary to define the time axis of a dataset and must be assigned to a variable list using `vlistDefTaxis`. The following different Time axis types are available:

<code>TAXIS_ABSOLUTE</code>	Absolute time axis
<code>TAXIS_RELATIVE</code>	Relative time axis

An absolute time axis has the current time to each time step. It can be used without knowledge of the calendar.

A relative time is the time relative to a fixed reference time. The current time results from the reference time and the elapsed interval. The result depends on the used calendar. CDI supports the following calendar types:

<code>CALENDAR_STANDARD</code>	Mixed Gregorian/Julian calendar.
<code>CALENDAR_PROLEPTIC</code>	Proleptic Gregorian calendar. This is the default.
<code>CALENDAR_360DAYS</code>	All years are 360 days divided into 30 day months.
<code>CALENDAR_365DAYS</code>	Gregorian calendar without leap years, i.e., all years are 365 days long.
<code>CALENDAR_366DAYS</code>	Gregorian calendar with every year being a leap year, i.e., all years are 366 days long.

4.8.1. Create a Time axis: `taxisCreate`

The function `taxisCreate` creates a Time axis.

Usage

```
int taxisCreate(int taxistype);
```

taxistype The type of the Time axis, one of the set of predefined **CDI** time axis types. The valid **CDI** time axis types are `TAXIS_ABSOLUTE` and `TAXIS_RELATIVE`.

Result

`taxisCreate` returns an identifier to the Time axis.

Example

Here is an example using `taxisCreate` to create a relative T-axis with a standard calendar.

```
#include "cdi.h"
...
int taxisID;
...
taxisID = taxisCreate(TAXIS_RELATIVE);
taxisDefCalendar(taxisID, CALENDAR_STANDARD);
taxisDefRdate(taxisID, 19850101);
taxisDefRtime(taxisID, 120000);
...
```

4.8.2. Destroy a Time axis: `taxisDestroy`

Usage

```
void taxisDestroy(int taxisID);
```

`taxisID` Time axis ID, from a previous call to `taxisCreate`

4.8.3. Define the reference date: `taxisDefRdate`

The function `taxisDefRdate` defines the reference date of a Time axis.

Usage

```
void taxisDefRdate(int taxisID, int rdate);
```

`taxisID` Time axis ID, from a previous call to `taxisCreate`

`rdate` Reference date (YYYYMMDD)

4.8.4. Get the reference date: `taxisInqRdate`

The function `taxisInqRdate` returns the reference date of a Time axis.

Usage

```
int taxisInqRdate(int taxisID);
```

`taxisID` Time axis ID, from a previous call to `taxisCreate` or `vlistInqTaxis`

Result

`taxisInqRdate` returns the reference date.

4.8.5. Define the reference time: `taxisDefRtime`

The function `taxisDefRtime` defines the reference time of a Time axis.

Usage

```
void taxisDefRtime(int taxisID, int rtime);
```

`taxisID` Time axis ID, from a previous call to `taxisCreate`

`rtime` Reference time (hhmmss)

4.8.6. Get the reference time: `taxisInqRtime`

The function `taxisInqRtime` returns the reference time of a Time axis.

Usage

```
int taxisInqRtime(int taxisID);
```

`taxisID` Time axis ID, from a previous call to `taxisCreate` or `vlistInqTaxis`

Result

`taxisInqRtime` returns the reference time.

4.8.7. Define the verification date: `taxisDefVdate`

The function `taxisDefVdate` defines the verification date of a Time axis.

Usage

```
void taxisDefVdate(int taxisID, int vdate);
```

`taxisID` Time axis ID, from a previous call to [taxisCreate](#)

`vdate` Verification date (YYYYMMDD)

4.8.8. Get the verification date: `taxisInqVdate`

The function `taxisInqVdate` returns the verification date of a Time axis.

Usage

```
int taxisInqVdate(int taxisID);
```

`taxisID` Time axis ID, from a previous call to [taxisCreate](#) or [vlistInqTaxis](#)

Result

`taxisInqVdate` returns the verification date.

4.8.9. Define the verification time: `taxisDefVtime`

The function `taxisDefVtime` defines the verification time of a Time axis.

Usage

```
void taxisDefVtime(int taxisID, int vtime);
```

`taxisID` Time axis ID, from a previous call to [taxisCreate](#)

`vtime` Verification time (hhmmss)

4.8.10. Get the verification time: `taxisInqVtime`

The function `taxisInqVtime` returns the verification time of a Time axis.

Usage

```
int taxisInqVtime(int taxisID);
```

`taxisID` Time axis ID, from a previous call to [taxisCreate](#) or [vlistInqTaxis](#)

Result

`taxisInqVtime` returns the verification time.

4.8.11. Define the calendar: `taxisDefCalendar`

The function `taxisDefCalendar` defines the calendar of a Time axis.

Usage

```
void taxisDefCalendar(int taxisID, int calendar);
```

taxisID Time axis ID, from a previous call to [taxisCreate](#)

calendar The type of the calendar, one of the set of predefined **CDI** calendar types. The valid **CDI** calendar types are CALENDAR_STANDARD, CALENDAR_PROLEPTIC, CALENDAR_360DAYS, CALENDAR_365DAYS and CALENDAR_366DAYS.

4.8.12. Get the calendar: taxisInqCalendar

The function `taxisInqCalendar` returns the calendar of a Time axis.

Usage

```
int taxisInqCalendar(int taxisID);
```

taxisID Time axis ID, from a previous call to [taxisCreate](#) or [vlistInqTaxis](#)

Result

`taxisInqCalendar` returns the type of the calendar, one of the set of predefined **CDI** calendar types. The valid **CDI** calendar types are CALENDAR_STANDARD, CALENDAR_PROLEPTIC, CALENDAR_360DAYS, CALENDAR_365DAYS and CALENDAR_366DAYS.

Bibliography

[ecCodes]

[API for GRIB decoding/encoding](#), from the European Centre for Medium-Range Weather Forecasts ([ECMWF](#))

[ECHAM]

[The atmospheric general circulation model ECHAM5](#), from the [Max Planck Institute for Meteorologie](#)

[GRIB]

[GRIB version 1](#), from the World Meteorological Organisation ([WMO](#))

[HDF5]

[HDF version 5](#), from the HDF Group

[NetCDF]

[NetCDF Software Package](#), from the [UNIDATA](#) Program Center of the University Corporation for Atmospheric Research

[MPIOM]

The ocean model MPIOM, from the [Max Planck Institute for Meteorologie](#)

[REMO]

The regional climate model REMO, from the [Max Planck Institute for Meteorologie](#)

A. Quick Reference

This appendix provide a brief listing of the C language bindings of the **CDI** library routines:

`cdiDefAttFlt`

```
int cdiDefAttFlt(int cdiID, int varID, const char *name, int type, int len,
                 const double *dp);
```

Define a floating point attribute

`cdiDefAttInt`

```
int cdiDefAttInt(int cdiID, int varID, const char *name, int type, int len,
                 const int *ip);
```

Define an integer attribute

`cdiDefAttTxt`

```
int cdiDefAttTxt(int cdiID, int varID, const char *name, int len, const char *tp);
```

Define a text attribute

`cdiDefKeyBytes`

```
int cdiDefKeyBytes(int cdiID, int varID, int key, const unsigned char *bytes,
                  int length);
```

Define a byte array from a key

`cdiDefKeyFloat`

```
int cdiDefKeyFloat(int cdiID, int varID, int key, double value);
```

Define a floating point value from a key

`cdiDefKeyInt`

```
int cdiDefKeyInt(int cdiID, int varID, int key, int value);
```

Define an integer value from a key

cdiDefKeyString

```
int cdiDefKeyString(int cdiID, int varID, int key, const char *string);
```

Define a string from a key

cdiInqAtt

```
int cdiInqAtt(int cdiID, int varID, int attnum, char *name, int *typep, int *lenp);
```

Get information about an attribute

cdiInqAttFlt

```
int cdiInqAttFlt(int cdiID, int varID, const char *name, int mlen, double *dp);
```

Get the value(s) of a floating point attribute

cdiInqAttInt

```
int cdiInqAttInt(int cdiID, int varID, const char *name, int mlen, int *ip);
```

Get the value(s) of an integer attribute

cdiInqAttTxt

```
int cdiInqAttTxt(int cdiID, int varID, const char *name, int mlen, char *tp);
```

Get the value(s) of a text attribute

cdiInqKeyBytes

```
int cdiInqKeyBytes(int cdiID, int varID, int key, unsigned char *bytes, int *length);
```

Get a byte array from a key

cdiInqKeyFloat

```
int cdiInqKeyFloat(int cdiID, int varID, int key, double *value);
```

Get a floating point value from a key

cdiInqKeyInt

```
int cdiInqKeyInt(int cdiID, int varID, int key, int *value);
```

Get an integer value from a key

cdiInqKeyString

```
int cdiInqKeyString(int cdiID, int varID, int key, char *string, int *length);
```

Get a string from a key

cdiInqNatts

```
int cdiInqNatts(int cdiID, int varID, int *nattsp);
```

Get number of attributes

gridCreate

```
int gridCreate(int gridtype, SizeType size);
```

Create a horizontal Grid

gridDefNP

```
void gridDefNP(int gridID, int np);
```

Define the number of parallels between a pole and the equator

gridDefXbounds

```
void gridDefXbounds(int gridID, const double *xbounds);
```

Define the bounds of a X-axis

gridDefXsize

```
void gridDefXsize(int gridID, SizeType xsize);
```

Define the number of values of a X-axis

gridDefXvals

```
void gridDefXvals(int gridID, const double *xvals);
```

Define the values of a X-axis

gridDefYbounds

```
void gridDefYbounds(int gridID, const double *ybounds);
```

Define the bounds of a Y-axis

gridDefYsize

```
void gridDefYsize(int gridID, SizeType ysize);
```

Define the number of values of a Y-axis

gridDefYvals

```
void gridDefYvals(int gridID, const double *yvals);
```

Define the values of a Y-axis

gridDestroy

```
void gridDestroy(int gridID);
```

Destroy a horizontal Grid

gridDuplicate

```
int gridDuplicate(int gridID);
```

Duplicate a horizontal Grid

gridInqNP

```
int gridInqNP(int gridID);
```

Get the number of parallels between a pole and the equator

gridInqSize

```
SizeType gridInqSize(int gridID);
```

Get the size of a Grid

gridInqType

```
int gridInqType(int gridID);
```

Get the type of a Grid

gridInqXbounds

```
SizeType gridInqXbounds(int gridID, double *xbounds);
```

Get the bounds of a X-axis

gridInqXsize

```
SizeType gridInqXsize(int gridID);
```

Get the number of values of a X-axis

gridInqXvals

```
SizeType gridInqXvals(int gridID, double *xvals);
```

Get all values of a X-axis

gridInqYbounds

```
SizeType gridInqYbounds(int gridID, double *ybounds);
```

Get the bounds of a Y-axis

gridInqYsize

```
SizeType gridInqYsize(int gridID);
```

Get the number of values of a Y-axis

gridInqYvals

```
SizeType gridInqYvals(int gridID, double *yvals);
```

Get all values of a Y-axis

streamClose

```
void streamClose(int streamID);
```

Close an open dataset

streamDefByteorder

```
void streamDefByteorder(int streamID, int byteorder);
```

Define the byte order

streamDefRecord

```
void streamDefRecord(int streamID, int varID, int levelID);
```

Define the next record

streamDefTimestep

```
int streamDefTimestep(int streamID, int tsID);
```

Define a timestep

streamDefVlist

```
void streamDefVlist(int streamID, int vlistID);
```

Define the variable list

streamInqByteorder

```
int streamInqByteorder(int streamID);
```

Get the byte order

streamInqFiletype

```
int streamInqFiletype(int streamID);
```

Get the filetype

streamInqTimestep

```
int streamInqTimestep(int streamID, int tsID);
```

Get timestep information

streamInqVlist

```
int streamInqVlist(int streamID);
```

Get the variable list

streamOpenRead

```
int streamOpenRead(const char *path);
```

Open a dataset for reading

streamOpenWrite

```
int streamOpenWrite(const char *path, int filetype);
```

Create a new dataset

streamReadVar

```
void streamReadVar(int streamID, int varID, double *data, SizeType *nmiss);
```

Read a variable

streamReadVarF

```
void streamReadVar(int streamID, int varID, float *data, SizeType *nmiss);
```

Read a variable

streamReadVarSlice

```
void streamReadVarSlice(int streamID, int varID, int levelID, double *data,  
                        SizeType *nmiss);
```

Read a horizontal slice of a variable

streamReadVarSliceF

```
void streamReadVarSliceF(int streamID, int varID, int levelID, float *data,  
                        SizeType *nmiss);
```

Read a horizontal slice of a variable

streamWriteVar

```
void streamWriteVar(int streamID, int varID, const double *data, SizeType nmiss);
```

Write a variable

streamWriteVarF

```
void streamWriteVarF(int streamID, int varID, const float *data, SizeType nmiss);
```

Write a variable

streamWriteVarSlice

```
void streamWriteVarSlice(int streamID, int varID, int levelID, const double *data,  
                        SizeType nmiss);
```

Write a horizontal slice of a variable

streamWriteVarSliceF

```
void streamWriteVarSliceF(int streamID, int varID, int levelID, const float *data,  
                        SizeType nmiss);
```

Write a horizontal slice of a variable

taxisCreate

```
int taxisCreate(int taxistype);
```

Create a Time axis

taxisDefCalendar

```
void taxisDefCalendar(int taxisID, int calendar);
```

Define the calendar

taxisDefRdate

```
void taxisDefRdate(int taxisID, int rdate);
```

Define the reference date

taxisDefRtime

```
void taxisDefRtime(int taxisID, int rtime);
```

Define the reference time

taxisDefVdate

```
void taxisDefVdate(int taxisID, int vdate);
```

Define the verification date

taxisDefVtime

```
void taxisDefVtime(int taxisID, int vtime);
```

Define the verification time

taxisDestroy

```
void taxisDestroy(int taxisID);
```

Destroy a Time axis

taxisInqCalendar

```
int taxisInqCalendar(int taxisID);
```

Get the calendar

taxisInqRdate

```
int taxisInqRdate(int taxisID);
```

Get the reference date

taxisInqRtime

```
int taxisInqRtime(int taxisID);
```

Get the reference time

taxisInqVdate

```
int taxisInqVdate(int taxisID);
```

Get the verification date

taxisInqVtime

```
int taxisInqVtime(int taxisID);
```

Get the verification time

vlistCat

```
void vlistCat(int vlistID2, int vlistID1);
```

Concatenate two variable lists

vlistCopy

```
void vlistCopy(int vlistID2, int vlistID1);
```

Copy a variable list

vlistCopyFlag

```
void vlistCopyFlag(int vlistID2, int vlistID1);
```

Copy some entries of a variable list

vlistCreate

```
int vlistCreate(void);
```

Create a variable list

vlistDefTaxis

```
void vlistDefTaxis(int vlistID, int taxisID);
```

Define the time axis

vlistDefVar

```
int vlistDefVar(int vlistID, int gridID, int zaxisID, int timetype);
```

Define a Variable

vlistDefVarCode

```
void vlistDefVarCode(int vlistID, int varID, int code);
```

Define the code number of a Variable

vlistDefVarDatatype

```
void vlistDefVarDatatype(int vlistID, int varID, int datatype);
```

Define the data type of a Variable

vlistDefVarMissval

```
void vlistDefVarMissval(int vlistID, int varID, double missval);
```

Define the missing value of a Variable

vlistDestroy

```
void vlistDestroy(int vlistID);
```

Destroy a variable list

vlistDuplicate

```
int vlistDuplicate(int vlistID);
```

Duplicate a variable list

vlistInqTaxis

```
int vlistInqTaxis(int vlistID);
```

Get the time axis

vlistInqVarCode

```
int vlistInqVarCode(int vlistID, int varID);
```

Get the Code number of a Variable

vlistInqVarDatatype

```
int vlistInqVarDatatype(int vlistID, int varID);
```

Get the data type of a Variable

vlistInqVarGrid

```
int vlistInqVarGrid(int vlistID, int varID);
```

Get the Grid ID of a Variable

vlistInqVarMissval

```
double vlistInqVarMissval(int vlistID, int varID);
```

Get the missing value of a Variable

vlistInqVarTsteptype

```
int vlistInqVarTsteptype(int vlistID, int varID);
```

Get the timestep type of a Variable

vlistInqVarZaxis

```
int vlistInqVarZaxis(int vlistID, int varID);
```

Get the Zaxis ID of a Variable

vlistNgrids

```
int vlistNgrids(int vlistID);
```

Number of grids in a variable list

vlistNvars

```
int vlistNvars(int vlistID);
```

Number of variables in a variable list

vlistNzaxis

```
int vlistNzaxis(int vlistID);
```

Number of zaxis in a variable list

zaxisCreate

```
int zaxisCreate(int zaxistype, int size);
```

Create a vertical Z-axis

zaxisDefLevels

```
void zaxisDefLevels(int zaxisID, const double *levels);
```

Define the levels of a Z-axis

zaxisDestroy

```
void zaxisDestroy(int zaxisID);
```

Destroy a vertical Z-axis

zaxisInqLevel

```
double zaxisInqLevel(int zaxisID, int levelID);
```

Get one level of a Z-axis

zaxisInqLevels

```
void zaxisInqLevels(int zaxisID, double *levels);
```

Get all levels of a Z-axis

zaxisInqSize

```
int zaxisInqSize(int zaxisID);
```

Get the size of a Z-axis

zaxisInqType

```
int zaxisInqType(int zaxisID);
```

Get the type of a Z-axis

B. Examples

This appendix contains complete examples to write, read and copy a dataset with the **CDI** library.

B.1. Write a dataset

Here is an example using **CDI** to write a NetCDF dataset with 2 variables on 3 time steps. The first variable is a 2D field on surface level and the second variable is a 3D field on 5 pressure levels. Both variables are on the same lon/lat grid.

```
#include <stdio.h>
#include "cdi.h"

int
5 main(void)
{
    enum
    {
        nlon = 12, // Number of longitudes
10    nlat = 6,    // Number of latitudes
        nlev = 5,  // Number of levels
        nts = 3,   // Number of time steps
    };
    SizeType nmiss = 0;
15    double lons[] = { 0, 30, 60, 90, 120, 150, 180, 210, 240, 270, 300, 330 };
    double lats[] = { -75, -45, -15, 15, 45, 75 };
    double levs[] = { 101300, 92500, 85000, 50000, 20000 };
    double var1[nlon * nlat];
    double var2[nlon * nlat * nlev];
20
    // Create a regular lon/lat grid
    int gridID = gridCreate(GRID_LONLAT, nlon * nlat);
    gridDefXsize(gridID, nlon);
    gridDefYsize(gridID, nlat);
25    gridDefXvals(gridID, lons);
    gridDefYvals(gridID, lats);

    // Create a surface level Z-axis
    int zaxisID1 = zaxisCreate(ZAXIS_SURFACE, 1);
30
    // Create a pressure level Z-axis
    int zaxisID2 = zaxisCreate(ZAXIS_PRESSURE, nlev);
    zaxisDefLevels(zaxisID2, levs);

    // Create a variable list
35    int vlistID = vlistCreate();

    // Define the variables
    int varID1 = vlistDefVar(vlistID, gridID, zaxisID1, TIME_VARYING);
40    int varID2 = vlistDefVar(vlistID, gridID, zaxisID2, TIME_VARYING);
```

```

// Define the variable names
vlistDefVarName(vlistID, varID1, "varname1");
vlistDefVarName(vlistID, varID2, "varname2");
45

// Create a Time axis
int taxisID = taxisCreate(TAXIS_ABSOLUTE);

// Assign the Time axis to the variable list
50 vlistDefTaxis(vlistID, taxisID);

// Create a dataset in netCDF format
int streamID = streamOpenWrite("example.nc", CDI_FILETYPE_NC);
if (streamID < 0)
55 {
    fprintf(stderr, "%s\n", cdiStringError(streamID));
    return 1;
}

// Assign the variable list to the dataset
60 streamDefVlist(streamID, vlistID);

// Loop over the number of time steps
for (int tsID = 0; tsID < nts; tsID++)
65 {
    // Set the verification date to 1985-01-01 + tsID
    taxisDefVdate(taxisID, 19850101 + tsID);
    // Set the verification time to 12:00:00
    taxisDefVtime(taxisID, 120000);
70 // Define the time step
    streamDefTimestep(streamID, tsID);

    // Init var1 and var2
    for (size_t i = 0; i < nlon * nlat; i++) var1[i] = 1.1;
75 for (size_t i = 0; i < nlon * nlat * nlev; i++) var2[i] = 2.2;

    // Write var1 and var2
    streamWriteVar(streamID, varID1, var1, nmiss);
    streamWriteVar(streamID, varID2, var2, nmiss);
80 }

// Close the output stream
streamClose(streamID);

85 // Destroy the objects
vlistDestroy(vlistID);
taxisDestroy(taxisID);
zaxisDestroy(zaxisID1);
zaxisDestroy(zaxisID2);
90 gridDestroy(gridID);

return 0;
}

```

B.1.1. Result

This is the `ncdump -h` output of the resulting NetCDF file `example.nc`.

```
netcdf example {
2 dimensions:
    lon = 12 ;
    lat = 6 ;
    lev = 5 ;
    time = UNLIMITED ; // (3 currently)
7 variables :
    double lon(lon) ;
        lon:long_name = "longitude" ;
        lon:units = "degrees_east" ;
        lon:standard_name = "longitude" ;
12    double lat(lat) ;
        lat:long_name = "latitude" ;
        lat:units = "degrees_north" ;
        lat:standard_name = "latitude" ;
17    double lev(lev) ;
        lev:long_name = "pressure" ;
        lev:units = "Pa" ;
    double time(time) ;
        time:units = "day as %Y%m%d.%f" ;
22    float varname1(time, lat, lon) ;
    float varname2(time, lev, lat, lon) ;
data:

    lon = 0, 30, 60, 90, 120, 150, 180, 210, 240, 270, 300, 330 ;
27    lat = -75, -45, -15, 15, 45, 75 ;

    lev = 101300, 92500, 85000, 50000, 20000 ;

    time = 19850101.5, 19850102.5, 19850103.5 ;
32 }
```

B.2. Read a dataset

This example reads the NetCDF file `example.nc` from [Appendix B.1](#).

```
#include <stdio.h>
#include "cdi.h"
3
int
main(void)
{
    enum
8    {
        nlon = 12, // Number of longitudes
        nlat = 6,  // Number of latitudes
        nlev = 5,  // Number of levels
        nts = 3,   // Number of time steps
13    };
    SizeType nmiss;
    double var1[nlon * nlat];
    double var2[nlon * nlat * nlev];
18    // Open the dataset
```

```

int streamID = streamOpenRead("example.nc");
if (streamID < 0)
{
    fprintf(stderr, "%s\n", cdiStringError(streamID));
23     return 1;
}

// Get the variable list of the dataset
28 int vlistID = streamInqVlist(streamID);

// Set the variable IDs
int varID1 = 0;
int varID2 = 1;

33 // Get the Time axis from the variable list
int taxisID = vlistInqTaxis(vlistID);

// Loop over the number of time steps
for (int tsID = 0; tsID < nts; tsID++)
38 {
    // Inquire the time step
    streamInqTimestep(streamID, tsID);

    // Get the verification date and time
43     int vdate = taxisInqVdate(taxisID);
    int vtime = taxisInqVtime(taxisID);
    printf("read timestep-%d:~date=%d~time=%d\n", tsID + 1, vdate, vtime);

    // Read var1 and var2
48     streamReadVar(streamID, varID1, var1, &nmiss);
    streamReadVar(streamID, varID2, var2, &nmiss);
}

// Close the input stream
53 streamClose(streamID);

return 0;
}

```

B.3. Copy a dataset

This example reads the NetCDF file `example.nc` from [Appendix B.1](#) and writes the result to a GRIB dataset by simple setting the output file type to `CDI_FILETYPE_GRB`.

```

#include <stdio.h>
#include <stdlib.h>
#include "cdi.h"
4
int
main(void)
{
9    // Open the input dataset
    int streamID1 = streamOpenRead("example.nc");
    if (streamID1 < 0)
    {

```

```

14     fprintf(stderr, "%s\n", cdiStringError(streamID1));
        return 1;
    }

    // Get the variable list of the dataset
19     int vlistID1 = streamInqVlist(streamID1);

    int nvars = vlistNvars(vlistID1);

    int varDataSize = 0;
    double *varData = NULL;
24     for (int varID = 0; varID < nvars; ++varID)
    {
        int varSize = vlistInqVarSize(vlistID1, varID);
        varDataSize = varSize > varDataSize ? varSize : varDataSize;
    }
29     varData = malloc((size_t) varDataSize * sizeof(double));
    if (!varData)
    {
        perror("cannot allocate temporary copying buffer");
        return EXIT_FAILURE;
34     }

    // Open the output dataset (GRIB format)
    int streamID2 = streamOpenWrite("example.grb", CDI_FILETYPE_GRB);
    if (streamID2 < 0)
39     {
        fprintf(stderr, "%s\n", cdiStringError(streamID2));
        return EXIT_FAILURE;
    }

44     int vlistID2 = vlistDuplicate(vlistID1);

    streamDefVlist(streamID2, vlistID2);

    // Loop over the input time steps
49     int tsID = 0;
    while (streamInqTimestep(streamID1, tsID))
    {
        // Define the output time step
        streamDefTimestep(streamID2, tsID);
54
        for (int varID = 0; varID < nvars; ++varID)
        {
            SizeType nmiss;
            // Read var
59            streamReadVar(streamID1, varID, varData, &nmiss);
            // Write var
            streamWriteVar(streamID2, varID, varData, nmiss);
        }
        ++tsID;
64     }

    // Close the streams
    streamClose(streamID1);
    streamClose(streamID2);
69

```

```
return EXIT_SUCCESS;  
}
```

C. Environment Variables

The following table describes the environment variables that affect **CDI**.

Variable name	Default	Description
CDI_CONVERT_CUBESPHERE	1	Convert cubed-sphere data to unstructured grid.
CDI_CHUNK_CACHE	0	Set the NetCDF4 chunk cache size.
CDI_CHUNK_CACHE_MAX	0	Set maximum chunk cache size.
CDI_GRIB1_TEMPLATE	None	Path to a GRIB1 template file for GRIB_API.
CDI_GRIB2_TEMPLATE	None	Path to a GRIB2 template file for GRIB_API.
CDI_INVENTORY_MODE	None	Set to time to skip double variable entries.
CDI_QUERY_ABORT	1	Abort if query entry not found
CDI_READ_CELL_CORNERS	1	Read grid cell corners.
CDI_SHUFFLE	0	Set shuffle option to NetCDF4 deflation compression.
CDI_VERSION_INFO	1	Set to 0 to disable NetCDF global attribute CDI.

Index

C

cdiDefAttFlt	34
cdiDefAttInt	33
cdiDefAttTxt	33
cdiDefKeyBytes	30
cdiDefKeyFloat	29
cdiDefKeyInt	29
cdiDefKeyString	27
cdiInqAtt	32
cdiInqAttFlt	34
cdiInqAttInt	34
cdiInqAttTxt	33
cdiInqKeyBytes	30
cdiInqKeyFloat	30
cdiInqKeyInt	29
cdiInqKeyString	28
cdiInqNatts	32

G

gridCreate	35
gridDefNP	37
gridDefXbounds	39
gridDefXsize	36
gridDefXvals	38
gridDefYbounds	39
gridDefYsize	37
gridDefYvals	38
gridDestroy	36
gridDuplicate	36
gridInqNP	38
gridInqSize	36
gridInqType	36
gridInqXbounds	39
gridInqXsize	37
gridInqXvals	38
gridInqYbounds	40
gridInqYsize	37
gridInqYvals	39

S

streamClose	15
streamDefByteorder	15
streamDefTimestep	16

streamDefVlist	16
streamInqByteorder	15
streamInqFiletype	15
streamInqTimestep	16
streamInqVlist	16
streamOpenRead	14
streamOpenWrite	13
streamReadVar	18
streamReadVarF	18
streamReadVarSlice	18
streamReadVarSliceF	19
streamWriteVar	17
streamWriteVarF	17
streamWriteVarSlice	17
streamWriteVarSliceF	18

T

taxisCreate	44
taxisDefCalendar	46
taxisDefRdate	45
taxisDefRtime	45
taxisDefVdate	46
taxisDefVtime	46
taxisDestroy	45
taxisInqCalendar	47
taxisInqRdate	45
taxisInqRtime	45
taxisInqVdate	46
taxisInqVtime	46

V

vlistCat	21
vlistCopy	20
vlistCopyFlag	21
vlistCreate	20
vlistDefTaxis	22
vlistDefVar	23
vlistDefVarCode	25
vlistDefVarDatatype	25
vlistDefVarMissval	26
vlistDestroy	20
vlistDuplicate	20
vlistInqTaxis	22

vlistInqVarCode	25
vlistInqVarDatatype	25
vlistInqVarGrid	24
vlistInqVarMissval	26
vlistInqVarTsteptype	24
vlistInqVarZaxis	24
vlistNgrids	21
vlistNvars	21
vlistNzaxis	21

Z

zaxisCreate	41
zaxisDefLevels	43
zaxisDestroy	42
zaxisInqLevel	43
zaxisInqLevels	43
zaxisInqSize	42
zaxisInqType	42